

GETTING STARTED

Before using the program, make a backup copy of the original disk. Operate the program using the backup and keep the original in a safe place.


This cloning program is designed to perform data setting and cloning for the dual band transceiver IC-207H.

To use this program, the following hardware and software are required:

- IBM PC/AT or PS/2 compatible computer with an RS-232C serial port
- MS-DOS, PC-DOS or IBM DOS ver. 5.02 or higher
- OPC-646 CLONING CABLE

CONNECTIONS

All cloning operations are performed from computer's keyboard including power ON — only connect to a DC power supply is needed for the transceiver.



INSTALLATION AND PROGRAM START UP

■ Installation and initial setup'

Connect the transceiver and PC as above then connect a DC power supply to the the transceiver.

To install the CS-207 cloning software to ICOM\CS207 directory of drive C while the program disk is in drive A, type as follows at the DOS prompt:

A:\INSTALL A: C:\ICOM\CS207 [Enter]

Program drive Target drive/directory

A target directory is created if it does not already exist; CS-207 cannot be installed to the root directory. After the installation is finished, the CS-207 initial setup screen appears and the transceiver model is checked. Proceed as follows:

- ① Select the connected RS-232C (COM1/COM2) port with the [**↑**]/[**↓**] and [Enter] keys.
- ② Input your call sign then push [Enter].
- ③ After the initial setup, CS-207 is automatically launched. Set or modify the data as desired.
 - See the back page for operation.
- ④ Use the File sub menu to save the data or to exit the program.

■ Starting the program

To start the program after installation, operate as follows at the DOS prompt:

- ① Change to the installed directory.
 - C:\ICOM\CS207 in case of the example at left.
- ② Type as follows to start:
CS207 [Enter] (at the installed directory)

■ Operating from a floppy disk

This program can be operated from a floppy disk.


- ① Insert the backup disk into the floppy disk drive.
- ② Select the floppy disk drive as the current drive.
- ③ Select the "CS207" directory.
- ④ Type "CS207," then push [Enter] to start.

■ NEVER remove the program disk from the floppy disk drive while the program is running.
■ NEVER set the floppy disk as write-protected.
Cloning will take 20 sec. or more when operating from a floppy disk.

MENU FLOW

Push [Alt] or [Esc] to select the TOP menu.

- The TOP menu lightens,
 - A screens and operations can be selected from the TOP menu.
- Push [F1] to call up the help message.



To select a SUB menu, push the highlighted key; or select with the [→]/[←] keys then push [Enter] or [↓].

The screen darkens when the TOP menu is selected.

	File	Screen	Clone	Print	SetUP
Load	Memory CH	Read <- TR	Current	Display Type	
Save	VFO	Write → TR	All	Wallpaper	
Delete	DTMF Autodial	Information		RS-232C	
Dos	Common			Call Sign	
Preset					
EXit					

	SUB MENU	DESCRIPTION	SUB MENU	DESCRIPTION
File	Load	Loads data from a saved file.	Clone	Read <- TR
	Save	Saves data to a desired file. File extension (.ICF) is added automatically.		Write → TR
	Delete	Deletes a file.		Information
	Dos	Allows you to use a DOS command. To return to the previous screen, type "EXIT" then push [Enter].	Print	Current
	Preset	Loads a preset file. Moves the cursor to the first memory channel for input in the V or U memory channel screen.		All
	EXit	Quits and exits the program, then returns to the DOS prompt.	SetUP	Display Type
Screen	Memory CH	Sets the operating frequency, duplex setting, etc. for call, memory and scan edge channels.		Wallpaper
	VFO	Sets the operating frequency, duplex setting, etc. for VFO.		RS- 232C
	DTMF Autodial	Sets the DTMF codes, DTMF transmission speed, etc.		Call Sign
	Common	Sets commonly used data, such as set mode settings, initial set mode settings, cloning comments, etc.		